



Tender specification:

All doors comply with the following standards and regulations:

**Lift Directive 2014/33/EU
EN 81-20/50**

Swing landing door with flap lock, two panel, centre opening with external hinges, last closing panel on right

Frame: folded sheet steel, 4.0 mm thick, primed, on right and left each 120 mm wide, transom height 150 mm

Door panels: folded sheet steel, 2.0 mm thick, primed

Sill: Angle profile 60x60x6 mm, primed

Vision panel: 100 x 300 mm, glazing with laminated safety glass

Vision panel frame: of aluminium, anodised EV1

Protection class: IP 67

Interlock: type-tested flap lock with single bearing block, roller level actuation parallel to the frame, position of roller lever in transom

Emergency release: according to EN 81-20 500 mm above finished floor level

Options:

Vision panel: 100 x 600 mm, glazing with laminated safety glass

Protection class: Explosion-proof design

Last closing panel: on left

Panel sectioning: asymmetric

Door design: 3- or 4-panel, symmetric or asymmetric panel sectioning

Fire safety: Design according to EN 81-58, with laminated safety glass pane and additional pane of Pyran S per panel, vision panel 100 x 300 mm

Fire safety: Design according to EN 81-58, with laminated safety glass pane and additional pane of Pyran S per panel, vision panel 100 x 600 mm

Powder coating: Door panel and frame, powder coated on all sides according to RAL

Door panel and door frame: manufactured completely of stainless steel 1.4301 (AISI 304) / 1.4571 (AISI 316), glass-bead blasted